



## PERAKUAN PEMATUHAN STANDARD (BAHAN BINAAN)

Adalah dengan ini Pengilang/Pengeluar yang dinyatakan di bawah ini telah mengeluarkan bahan binaan yang diperakui oleh Lembaga mengikut Bahagian VIIA Akta Lembaga Pembangunan Industri Pembinaan Malaysia (Pindaan 2011). Perakuan ini adalah tertakluk kepada syarat-syarat yang telah ditetapkan. Perakuan ini mengesahkan bahawa bahan atau produk binaan yang dinyatakan di bawah telah diperakukan

No. Pendaftaran : 1181015PK0312  
Nama Pengilang / Pengeluar : UAC BERHAD  
Alamat Kilang Berdaftar : 36, JALAN PORTLAND  
TASEK INDUSTRIAL ESTATE 31400 IPOH  
PERAK

### Kategori Bahan Binaan :

#### **FIBRE CEMENT FLAT SHEET**

(Rujuk LAMPIRAN A untuk butiran terperinci bahan atau produk binaan yang diperakukan )

Tarikh Mula Berkuatkuasa : 22-10-2025  
Tarikh Tamat Tempoh Perakuan : 21-10-2026

Perakuan ini boleh diperbaharui bermula 60 hari sebelum tarikh tamat tempoh perakuan.

Nota: Perakuan dikeluarkan setelah Lembaga menjalankan pemeriksaan dan pengesahan ke atas kilang dan produk-produk yang terkandung di dalam Pensijilan Produk (Product Certification) yang dikeluarkan oleh Badan Pensijilan yang diiktiraf. Pihak pengeluar/pengilang adalah bertanggungjawab untuk memastikan Pensijilan Produk (Product Certification) sentiasa dalam tempoh sahlaku.

**MOHAMMAD FARRIS ABDUL AZIZ**  
**PENGARAH**  
**CIDB NEGERI PERAK**  
b.p Ketua Eksekutif



**SIJIL INI ADALAH CETAKAN KOMPUTER DAN TIDAK MEMERLUKAN TANDATANGAN**

## SYARAT - SYARAT PERAKUAN PEMATUHAN STANDARD (PPS)

### 1. Syarat-syarat

- a) Perakuan ini tidak boleh dipindah milik.
- b) Lembaga berhak mengenakan apa-apa arahan berkenaan bahan binaan dan standard yang didaftarkan dalam PPS ini dari semasa ke semasa.
- c) Lembaga berhak pada bila-bila masa menjalankan pemeriksaan terhadap mana-mana pihak yang berurusan dengan mana-mana bahan binaan yang terkandung dalam Jadual Keempat.

### 2. Tanggungjawab Pemilik Sijil PPS

- a) Memahami dan mematuhi peruntukan-peruntukan Akta Lembaga Pembangunan Industri Pembinaan Malaysia 1994 Akta 520 (Pindaan 2011), peraturan-peraturan yang dibuat di bawahnya dan apa-apa terma, syarat-syarat atau sekatan yang dikenakan oleh Lembaga dari semasa ke semasa.
- b) Tidak boleh berurusan atau mengaku janji untuk berurusan, sama ada secara langsung atau tidak langsung, dengan bahan binaan yang dinyatakan dalam Jadual Keempat, melainkan jika bahan binaan itu telah diperakuan dan memperolehi PPS yang masih sah (belum tamat tempoh).
- c) Memastikan Sijil Produk/ Keputusan Pengujian Penuh yang dikeluarkan oleh Badan Pensijilan yang diiktiraf bagi bahan binaan yang diperakuan dalam perakuan ini sentiasa dalam tempoh sah laku.
- d) Mengemukakan Salinan sijil PPS ini kepada pembeli semasa urusan pembekalan, pemasaran, pemindahan dan penjualan sebagai bukti bahan binaan ini telah diperakui oleh Lembaga.
- e) Sentiasa memberi kerjasama dalam mengemukakan apa-apa maklumat yang dikehendaki oleh Lembaga dari semasa ke semasa.
- f) Memaklumkan kepada Lembaga jika ingin menamatkan, memindahkan atau apa-apa perubahan berkaitan operasi dan lokasi.
- g) Memahami dan bertanggungjawab terhadap produk-produk yang memerlukan pematuhan standard yang berterusan (pembaharuan) terutama yang melibatkan kualiti dan keselamatan kerja-kerja pembinaan, pekerja dan orang awam (Contoh; perancah, konkrit siap banchuh atau lain-lain yang berkaitan)

### 3. Tindakan Atas Perlanggaran Akta 520 CIDB

- a) Lembaga boleh mengambil tindakan pendakwaan mahkamah kepada mana-mana orang yang melanggar mana-mana peruntukan dalam Akta 520 dan apabila disabitkan, didenda tidak kurang daripada sepuluh ribu ringgit (RM10,000) tetapi tidak melebihi lima ratus ribu ringgit (RM500,000).
- b) Lembaga juga boleh mengenakan tindakan tatatertib terhadap mana-mana ketidakpatuhan yang dilakukan seperti berikut:-

Bil	Kesalahan	Hukuman
1	Berurusan dengan PPS yang tamat tempoh	Gantung, Batal PPS atau dikenakan penalti denda tidak lebih RM10,000 atau mana-mana tindakan gantung atau batal dan juga dikenakan penalti denda tidak lebih RM10,000
2	Memalsu atau mengubahsuai sijil PPS, Pensijilan Produk (PC), Keputusan Pengujian Penuh (FTTR) atau apa-apa dokumen berkaitan bagi maksud memperakui bahan binaan tersebut	
3	Melakukan apa-apa ketidakpatuhan terhadap bahan binaan yang diperiksa atau berdasarkan keputusan ujian atau kedua-duanya	
4	Melanggar mana-mana arahan Lembaga, akujanji atau akuan tanggungjawab yang dikeluarkan	
5	Berurusan dengan mana-mana bahan binaan yang tiada di dalam senarai sijil PPS	
6	Walau bagaimanapun bagi PC yang telah digantung, dibatal atau lain-lain tindakan oleh Badan Pensijilan (CB)	PPS tersebut akan digantung atau dibatalkan
7	Pemohon membatalkan atau menggantung PPS secara sukarela	

- c) Lembaga tidak akan bertanggungjawab terhadap apa-apa kerugian atau kos-kos yang terlibat hasil dari tindakan ketidakpatuhan yang dilakukan dan ianya merupakan tanggungjawab pengeluar, pengilang atau mana-mana orang yang berurusan sepenuhnya.

**Catatan :** PPS yang telah diputuskan dan dibatalkan oleh Jawatankuasa tatatertib tidak boleh diperbaharui sehingga tempoh maksima 2 tahun. Perlanggaran arahan tersebut dan masih berurusan dengan bahan yang tidak diperakuan akan mengakibatkan pemohon disenarai hitam dari memohon PPS selamanya dan tindakan pendakwaan mahkamah dengan denda maksima RM500,000.

No. Pendaftaran : 1181015PK0312  
 Nama Pengilang / Pengeluar : UAC BERHAD

Kategori	Jenis / Saiz	Jenama	Standard
FIBRE CEMENT FLAT SHEET	Non Asbestos Fibre Cement Flat Sheets Superflex, Flexabord, Vistabord, Multiflex, Duravent, Lattice, Shingles, Angkasa, Chemerah Plus, Forra Plus, Tika, Plank Smooth, Plank Sedartex Woodgrain, Supertex Panel Woodgrain / LxW: 2440x1220, 1220x1220, 1220x610, 2250x1220, 3660x230, 3600x225, 2250x600, 610x610 (THK: 3.2,3.5,4.5,6.0,7.5,9.0,12.0,15.0,18.0,19.0,20.0,22.0,25.0)	UAC	MS 1296:2010
	Non Asbestos Fibre Cement Flat Sheets Model: DecoWood (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 75 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm	UAC	MS 1296:2010
	Non Asbestos Fibre Cement Flat Sheets Model: DecoWood (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 100 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm	UAC	MS 1296:2010

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: DecoWood (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 150 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: DecoWood (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 200 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: DecoWood (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 300 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Skirting (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 100 mm; Thickness: 9.0 mm, 12.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Plank Shiplap (Sedartex Woodgrain); Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 3660 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm

---



Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Fence (Smooth); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 1830 mm x 115 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: DecoWood Premium (Smooth & Woodlike); Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 150 mm; Thickness: 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Superflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2440 mm x 1220 mm; Thickness: 3.2 mm, 3.5 mm, 4.5 mm, 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Superflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 1200 mm; Thickness: 3.2 mm, 3.5 mm, 4.5 mm, 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Superflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 1220 mm x 1220 mm; Thickness: 3.2 mm, 3.5 mm, 4.5 mm, 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat      UAC      MS 1296:2010  
Sheets  
Model: Superflex; Rating: Category  
A Class 2 Level I; Type: Non  
Textured Sheets; Length and  
Width: 1220 mm x 610 mm;  
Thickness: 3.2 mm, 3.5 mm, 4.5  
mm, 6.0 mm, 7.5 mm, 9.0 mm,  
12.0 mm, 15.0 mm, 18.0 mm, 20.0  
mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat      UAC      MS 1296:2010  
Sheets  
Model: Superflex; Rating: Category  
A Class 2 Level I; Type: Non  
Textured Sheets; Length and  
Width: 1213 mm x 603 mm;  
Thickness: 3.2 mm, 3.5 mm, 4.5  
mm, 6.0 mm, 7.5 mm, 9.0 mm,  
12.0 mm, 15.0 mm, 18.0 mm, 20.0  
mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat      UAC      MS 1296:2010  
Sheets  
Model: Superflex; Rating: Category  
A Class 2 Level I; Type: Non  
Textured Sheets; Length and  
Width: 603 mm x 603 mm;  
Thickness: 3.2 mm, 3.5 mm, 4.5  
mm, 6.0 mm, 7.5 mm, 9.0 mm,  
12.0 mm, 15.0 mm, 18.0 mm, 20.0  
mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat      UAC      MS 1296:2010  
Sheets  
Model: Superflex; Rating: Category  
A Class 2 Level I; Type: Non  
Textured Sheets; Length and  
Width: 595 mm x 595 mm;  
Thickness: 3.2 mm, 3.5 mm, 4.5  
mm, 6.0 mm, 7.5 mm, 9.0 mm,  
12.0 mm, 15.0 mm, 18.0 mm, 20.0  
mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Superflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 1195 mm x 595 mm; Thickness: 3.2 mm, 3.5 mm, 4.5 mm, 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Superflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 610 mm x 610 mm; Thickness: 3.2 mm, 3.5 mm, 4.5 mm, 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm, 15.0 mm, 18.0 mm, 20.0 mm, 25.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Flexabord; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2440 mm x 1220 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Flexabord; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 1200 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
 Model: Vistabord; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2440 mm x 1220 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm

---

Non Asbestos Fibre Cement Flat Sheets Model: Vistabord; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 1200 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Multiflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2440 mm x 1220 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Multiflex; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2400 mm x 1200 mm; Thickness: 6.0 mm, 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Duravent; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 1220 mm x 1220 mm; Thickness: 3.2 mm, 4.5 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Duravent; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 1220 mm x 610 mm; Thickness: 3.2 mm, 4.5 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Lattice; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 2440 mm x 1220 mm; Thickness: 6.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Smooth; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 3660 mm x 230 mm; Thickness: 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Smooth; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 3600 mm x 225 mm; Thickness: 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Smooth; Rating: Category A Class 2 Level I; Type: Non Textured Sheets; Length and Width: 3660 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm, 12.0 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Angkasa; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 1220 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Angkasa; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 610 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Chemerah Plus; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 1220 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Chemerah Plus; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 610 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Forra Plus; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 1220 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
---	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Forra Plus; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 1220 mm x 610 mm; Thickness: 3.2 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Sedartex Woodgrain; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 3660 mm x 230 mm; Thickness: 6.5 mm, 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Sedartex Woodgrain; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 3660 mm x 160 mm; Thickness: 6.5 mm, 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Plank Sedartex Woodgrain; Rating: Category A Class 2 Level I; Type: Textured Sheets; Length and Width: 3660 mm x 210 mm; Thickness: 6.5 mm, 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------



Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: Supertex Panel Woodgrain;  
Rating: Category A Class 2 Level I;  
Type: Textured Sheets; Length and  
Width: 2440 mm x 1216 mm;  
Thickness: 6.0 mm

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: DecoWood (Smooth &  
Woodlike); Rating: Category A  
Class 2 Level I, Type: Non  
Textured Sheets; Length and  
Width: 2400 mm x 50 mm;  
Thickness: 6.0 mm, 7.5 mm, 9.0  
mm, 12.0 mm, 15.0 mm, 18.0 mm,  
20.0 mm, 25.0 mm

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: Plank Shiplap (Smooth);  
Rating: Category A Class 2 Level I,  
Type: Non Textured Sheets; Length  
and Width: 3660 mm x 150 mm;  
Thickness: 7.5 mm, 9.0 mm

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: Fence (Smooth); Rating:  
Category A Class 2 Level I, Type:  
Non Textured Sheets; Length and  
Width: 1220 mm x 115 mm;  
Thickness: 7.5 mm, 9.0 mm

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: Fence (Smooth); Rating:  
Category A Class 2 Level I, Type:  
Non Textured Sheets; Length and  
Width: 1220 mm x 150 mm;  
Thickness: 7.5 mm, 9.0 mm

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010

Model: Fence (Smooth); Rating:  
Category A Class 2 Level I, Type:  
Non Textured Sheets; Length and  
Width: 1220 mm x 160 mm;  
Thickness: 7.5 mm, 9.0 mm

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Smooth); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length and Width: 1830 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Smooth); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length and Width: 1830 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Smooth); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length and Width: 2440 mm x 115 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Smooth); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length and Width: 2440 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Smooth); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length and Width: 2440 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1220 mm x 115 mm; Thickness: 7.5 mm, 9.0 mm	UAC	MS 1296:2010
--	-----	--------------

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1220 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1220 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1830 mm x 115 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1830 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 1830 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 2440 mm x 115 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 2440 mm x 150 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: Fence (Sedartex Woodgrain); Rating: Category A Class 2 Level I, Type: Textured Sheets; Length and Width: 2440 mm x 160 mm; Thickness: 7.5 mm, 9.0 mm

---

Non Asbestos Fibre Cement Flat Sheets UAC MS 1296:2010  
Model: DecoWood Premium (Smooth & Woodlike); Rating: Category A Class 2 Level I, Type: Non Textured Sheets; Length & Width: 2400 mm x 200 mm; Thickness: 20.0 mm, 25.0 mm

---